

# MATERIAL SAFETY DATA SHEET

FULL CIRCLE Soil Retardant Spin Bonnet Carpet Cleaner with DuPont

Teflon

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name/Use: FULL CIRCLE Soil Retardant Spin Bonnet Carpet Cleaner with DuPont Teflon

**MANUFACTURER** 

The Butcher Company 67 Forest Street Marlborough, MA 01752-3012 Butcher Telephone Number: 800-225-9475

Emergency Telephone (24 hours): 800-228-5635 Ext 118

Date Prepared: 12/02/1997

## 2. COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENT(S)	CAS NO.	% BY WEIGHT	
2-Butoxyethanol	111-76-2	7 - 10	
Isopropyl alcohol	67-63-0	3 - 5	
Naphthalene sodium sulfonate	26264-58-4	1 - 3	

See Section 8 for Exposure Limits NA - Not Applicable

## 3. HAZARDS IDENTIFICATION

## **EMERGENCY OVERVIEW**

Clear, Light Straw Colored Liquid. Fresh Odor. May Cause Eye Irritation. Combustible.

POTENTIAL HEALTH EFFECTS (See Section 11 for Toxicological Information)

PRIMARY ROUTE(s) OF EXPOSURE: X Eye X Skin Contact Skin Absorption X Inhalation X Ingestion

## EFFECTS OF ACUTE EXPOSURE

#### EYES:

May cause eye irritation. Symptoms may include redness and pain.

#### SKIN:

May cause mild skin irritation. Symptoms may include redness.

#### INHALATION:

High concentrations of vapor or mist may cause nose, throat and respiratory tract irritation. Symptoms may include coughing, wheezing and shortness of breath. High concentrations of vapor or mist may also cause central nervous system effects including headache, dizziness and nausea.

## INGESTION:

May cause mouth, throat and stomach irritation. Symptoms may include nausea, vomiting and diarrhea. May also cause central nervous system effects including headache, dizziness and weakness.

MSDS No: 4077 Page: 1 of 7

#### EFFECTS OF CHRONIC EXPOSURE:

Prolonged or repeated contact can cause defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

Date Prepared: 12/02/1997 Date Revised: 12/09/1997

#### MEDICAL CONDITIONS AGGRAVATED:

May aggravate pre-existing eye, skin and respiratory conditions.

#### 4. FIRST AID MEASURES

#### EYES:

Flush eyes with plenty of water while holding eyelids apart. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Do not put any medication in the victim's eyes unless instructed by a physician. Get medical attention.

#### SKIN:

Flush with water, then wash with soap and water. Remove saturated clothing. Get medical attention if irritation develops.

#### INHALATION:

Remove to fresh air. If not breathing, give respiration; if breathing is difficult, give oxygen (by trained personnel only). Get medical attention if symptoms persist.

## **INGESTION:**

Do not induce vomiting. Drink large quantities of water. Get immediate medical attention. Never give anything by mouth to an unconscious person.

#### 5. FIRE FIGHTING MEASURES

FLASH POINT AND METHOD: 132°F 54.4°C TCC

## FLAMMABLE LIMITS

UPPER EXPLOSIVE LIMIT: 12.7% (isopropyl alcohol) LOWER EXPLOSIVE LIMIT: 2% (isopropyl alcohol)

AUTOIGNITION TEMPERATURE: Not applicable.

#### **EXTINGUISHING MEDIA:**

Use water fog, dry chemical, CO2, or foam.

## HAZARDOUS COMBUSTION PRODUCTS:

Normal products of combustion (carbon monoxide and carbon dioxide).

#### FIRE AND EXPLOSION HAZARDS:

Class II combustible liquid. This product is combustible and may be ignited by heat, sparks, flame, and other ignition sources. Vapors can travel to a source of ignition and flash back.

MSDS No: 4077 Page: 2 of 7

Date Prepared: 12/02/1997 Date Revised: 12/09/1997

#### FIRE FIGHTING INSTRUCTIONS:

Evacuate area. Cool containers exposed to fire with water. MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full protective gear should be worn.

## 6. ACCIDENTAL RELEASE MEASURES

See Section 8, Exposure Controls/Personal Protection and Section 3, Hazard Identification. Floors may be slippery. Use care to avoid falling. Remove ignition sources and ventilate spill area. Contain and isolate spill. Keep non-essential personnel from entering spill area. Use mop, absorbent and non-sparking tools to collect material for proper disposal. Rinse area with water.

# 7. HANDLING AND STORAGE

#### HANDLING:

Follow label use directions. Do not mix with other chemicals unless instructed by label directions. Avoid contact with eyes, skin and clothing. Use with adequate ventilation. Avoid breathing vapor or mist. Use spark-proof tools. Wash thoroughly after handling. Remove contaminated clothing. Wash clothing and equipment before reuse.

## STORAGE:

Keep container closed when not in use. Store away from incompatible materials. (See Section 10, Stability and Reactivity). Store away from direct sunlight. Keep away from heat, sparks and flame.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

## PERSONAL PROTECTIVE EQUIPMENT (PPE)

#### EYE:

Where eye contact is possible, wear safety glasses with side shields or chemical splash goggles (ANSI Z87.1 approved).

#### SKIN:

Where prolonged or repeated contact is possible, chemical-resistant clothing (e.g., gloves) is recommended.

## RESPIRATORY:

No respiratory protection is required if ventilation is adequate and airborne concentrations are kept below exposure limits. When exposure limits may be exceeded, use appropriate respiratory protection (NIOSH)/MSHA-approved) to prevent overexposure.

#### **ENGINEERING CONTROLS:**

General room ventilation is expected to be adequate. If user operations generate vapor or mist, ventilation should be used to keep airborne concentrations below exposure limits.

MSDS No: 4077 Page: 3 of 7

Date Prepared: 12/02/1997 Date Revised: 12/09/1997

**EXPOSURE LIMITS:** 

INGREDIENT(S)

OSHA PEL/STEL

2-Butoxyethanol

OSHA PEL/STEL

25 ppm (120 mg/m3)/

25 ppm (121 mg/m3)/

(Skin) (Skin)

Isopropyl alcohol 400 ppm (980 mg/m3)/ 400 ppm (983 mg/m3)/

500 ppm (1225 mg/m3) 500 ppm (1230 mg/m3)

Naphthalene sodium sulfonate NE NE

NE - Not Established

## 9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Fresh

APPEARANCE: Clear, Light Straw Colored

pH: 6.8 to 7.2

PERCENT VOLATILE BY WEIGHT: 98 VAPOR PRESSURE: Not Determined VAPOR DENSITY: Not Determined BOILING POINT: Not Determined

FREEZING/MELTING POINT: Not Determined

SOLUBILITY IN WATER: Complete EVAPORATION RATE: Not Determined

SPECIFIC GRAVITY: 1.003 VISCOSITY: Water Thin

OCTANOL/WATER PARTITION COEFFICIENT: Not Determined

ODOR THRESHOLD: Not Determined

## 10. STABILITY AND REACTIVITY

## STABILITY (CONDITIONS TO AVOID):

Stable.

#### POLYMERIZATION:

Will not occur.

#### HAZARDOUS DECOMPOSITION:

None.

#### INCOMPATIBLE MATERIALS:

Oxidizers (e.g., bleach).

## 11. TOXICOLOGICAL INFORMATION

#### **ACUTE DATA:**

Based on testing of a similar product, this product may cause eye irritation; it is not considered to be toxic by inhalation. The following data are available for product ingredients.

MSDS No: 4077 Page: 4 of 7

Date Prepared: 12/02/1997 Date Revised: 12/09/1997

PRODUCT/INGREDIENT	ORAL LD <sub>50</sub> (rat)	DERMAL LD <sub>50</sub> (rabbit)	INHALATION LC <sub>50</sub> (rat)
2-Butoxyethanol	470 mg/kg	220 mg/kg	450 ppm (4-hr)
Isopropyl alcohol	5840 mg/kg	13000 mg/kg	12000 ppm (8-hr)
Naphthalene sodium sulfonate	Not Available	Not Available	Not Available

#### SENSITIZATION DATA:

No data available.

## CHRONIC DATA:

Prolonged overexposure to isopropyl alcohol by ingestion and inhalation has caused central nervous system effects in humans and laboratory animals; overexposure by ingestion has also caused liver effects in animals. Prolonged overexposure to high concentrations of 2-butoxyethanol has caused blood, liver and kidney effects in laboratory animals.

#### REPRODUCTIVE/TERATOGENIC DATA:

Ingestion of isopropyl alcohol has caused slight fetotoxic and reproductive effects in laboratory animals.

## CARCINOGENIC/MUTAGENIC DATA:

Not listed as carcinogenic by NTP, IARC, or ACGIH or regulated as a carcinogen by OSHA.

#### SYNERGISTIC MATERIALS:

No data available.

## 12. ECOLOGICAL INFORMATION

This product is made with all biodegradable detergents. No other data available.

## 13. DISPOSAL CONSIDERATIONS

Disposal of this material should be in accordance with local, state or provincial and federal regulations. The unused product, as manufactured, is a RCRA hazardous waste (Ignitable-D001) in accordance with 40 CFR 261. The product has not been evaluated by the Toxicity Characteristic Leachate Procedure (TCLP). According to RCRA, it is the responsibility of the waste generator to ensure proper disposal.

# 14. TRANSPORT INFORMATION

DOT/TDG HAZARDOUS MATERIAL DESCRIPTION: Not regulated when in a container of 119 gallons (454 liters) or less.

#### 15. REGULATORY INFORMATION

Not meant to be all-inclusive—selected regulations represented.

MSDS No: 4077 Page: 5 of 7

#### UNITED STATES

## SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

- 311/312 HAZARD CATEGORIES: Under 40 CFR 370.2, this product meets the following hazard categories: Immediate, Delayed, Fire.
- 313 REPORTABLE INGREDIENTS: 2-Butoxyethanol is subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372 under the chemical category Glycol Ethers.

## CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

CERCLA REGULATORY: None of the ingredients in this product are reportable under CERCLA.

#### TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA STATUS: This product complies with all TSCA inventory requirements.

## MASSACHUSETTS, NEW JERSEY, PENNSYLVANIA RIGHT-TO-KNOW:

INGREDIENT(S)	CAS NO.	STATE LISTING
Water	7732-18-5	Not Listed
2-Butoxyethanol	111-76-2	MA, NJ, PA
Isopropyl alcohol	67-63-0	MA, NJ, PA
Naphthalene sodium sulfonate	26264-58-4	Not Listed

NA - Not Applicable

#### CANADA

## WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM):

Class B-Division 3, combustible liquid; Class D-Division 2B, eye and skin irritant. This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.


#### OTHER INFORMATION 16.

#### **HMIS RATING**

HEALTH	*	2
FLAMMABILITY		2
REACTIVITY		0
PERSONAL PROTECTION		-

#### NFPA RATING

Date Prepared: 12/02/1997 Date Revised: 12/09/1997



MSDS STATUS New MSDS

MSDS No: 4077 Page: 6 of 7

Date Prepared: 12/02/1997 Date Revised: 12/09/1997

APPROVED BY: EH&S/Regulatory Affairs APPROVAL DATE: 12/09/1997

The information on this data sheet represents our current data and best opinion as to the proper use in handling of the product under normal foreseeable conditions. Any use of this product which is not in conformance with this data sheet or product label, or which involves using the product in combination with any other product or any other process is the responsibility of the user.

MSDS No: 4077 Page: 7 of 7