

MATERIAL SAFETY DATA SHEET

14 HEAD START Carpet Prespray

Date Prepared: 08/17/2000 Date Revised: 10/26/2000 Concentrate

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name/Use: 14 HEAD START Carpet Prespray Concentrate

Product Synonyms: Command Center 14 HEAD START Carpet Prespray Concentrate;

Outpost 14 HEAD START Carpet Prespray Concentrate; Command Center CARPET PRESPRAY Concentrate 14

MANUFACTURER

The Butcher Company 67 Forest Street

Marlborough, MA 01752-3012

Butcher Telephone Number: 800-225-9475 Emergency Telephone (24 hours): 800-228-5635

CHEMTREC (U.S./Can.): 800-424-9300 CHEMTREC (Int'l): +1 703-527-3887

2. COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENT(S)	CAS NO.	% BY WEIGHT	
Naphthalene sodium sulfonate	26264-58-4	40 - 60	
2-Butoxyethanol	111-76-2	25 - 40	
Alcohol ethoxylate	68439-50-9	7 - 10	

See Section 8 for Exposure Limits NA - Not Applicable

OSHA REGULATORY STATUS: This product is classified as hazardous under OSHA regulations.

WHMIS CLASS: Class D- Division 2B

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Clear, Amber Liquid. Herbal Odor. Causes Eye Irritation. May Be Harmful if Swallowed.

POTENTIAL HEALTH EFFECTS (See Section 11 for Toxicological Information)

X Skin Contact X Skin Absorption PRIMARY ROUTE(s) OF EXPOSURE: X Eye X Inhalation X Ingestion

EFFECTS OF ACUTE EXPOSURE

Causes eye irritation. Symptoms may include redness and pain.

SKIN:

May cause mild skin irritation. Symptoms may include redness. May be absorbed through the skin and may cause effects as described under Inhalation (see below).

MSDS No: 4081 Page: 1 of 7

Date Prepared: 08/17/2000 Date Revised: 10/26/2000

INHALATION:

High concentrations of vapor or mist may cause nose, throat and respiratory tract irritation. Symptoms may include coughing and a disagreeable metallic taste. High concentrations of vapor or mist may also cause central nervous system effects including headache, dizziness and nausea.

INGESTION:

May be harmful if swallowed. May cause mouth, throat and stomach irritation. Symptoms may include nausea, vomiting and diarrhea. May also cause central nervous system effects including headache, dizziness and weakness.

EFFECTS OF CHRONIC EXPOSURE:

Prolonged or repeated contact may cause skin irritation.

MEDICAL CONDITIONS AGGRAVATED:

May aggravate pre-existing eye, skin and respiratory conditions.

4. FIRST AID MEASURES

EYES:

Flush eyes with plenty of water while holding eyelids apart. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Do not put any medication in the victim's eyes unless instructed by a physician. Get medical attention.

SKIN:

Flush with water, then wash with soap and water. Remove saturated clothing. Get medical attention if irritation develops.

INHALATION:

Remove to fresh air. If not breathing, give respiration; if breathing is difficult, give oxygen (by trained personnel only). Get medical attention if symptoms persist.

INGESTION:

Do not induce vomiting. Drink large quantities of water. Get immediate medical attention. Never give anything by mouth to an unconscious person.

5. FIRE FIGHTING MEASURES

FLASH POINT AND METHOD: >200°F 93°C TCC

FLAMMABLE LIMITS:

Not applicable.

AUTOIGNITION TEMPERATURE: Not applicable.

EXTINGUISHING MEDIA:

Use extinguishing media appropriate for surrounding fire.

MSDS No: 4081 Page: 2 of 7

Date Prepared: 08/17/2000 Date Revised: 10/26/2000

HAZARDOUS COMBUSTION PRODUCTS:

Normal products of combustion (carbon monoxide and carbon dioxide) and sulfur oxides.

FIRE AND EXPLOSION HAZARDS:

None known.

FIRE FIGHTING INSTRUCTIONS:

This product is not flammable. As in any fire, MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full protective gear should be worn.

6. ACCIDENTAL RELEASE MEASURES

See Section 8, Exposure Controls/Personal Protection and Section 3, Hazard Identification. Floors may be slippery. Use care to avoid falling. Ventilate spill area. Contain and isolate spill. Keep non-essential personnel from entering spill area. Use mop, absorbent, or wet vacuum to collect material for proper disposal. Rinse area with water.

7. HANDLING AND STORAGE

HANDLING:

Follow label use directions. Do not mix with other chemicals unless instructed by label directions. Avoid contact with eyes. Avoid breathing vapor or mist. Wash thoroughly after handling. Remove saturated clothing. Wash clothing and equipment before reuse.

STORAGE:

Keep container closed when not in use. Store away from incompatible materials. (See Section 10, Stability and Reactivity).

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT (PPE)

EYE:

Where eye contact is possible, wear safety glasses with side shields or chemical splash goggles (ANSI Z87.1 approved).

SKIN:

Where prolonged or repeated contact is possible, chemical-resistant clothing (e.g., gloves) is recommended.

RESPIRATORY:

No respiratory protection is required if ventilation is adequate and airborne concentrations are kept below exposure limits. When exposure limits may be exceeded, use appropriate respiratory protection (NIOSH)/MSHA-approved) to prevent overexposure.

ENGINEERING CONTROLS:

Good general room ventilation is expected to be adequate. If user operations generate vapor or mist, ventilation should be used to keep airborne concentrations below exposure limits.

MSDS No: 4081 Page: 3 of 7

Date Prepared: 08/17/2000 Date Revised: 10/26/2000

EXPOSURE LIMITS:

INGREDIENT(S) OSHA PEL/STEL ACGIH TLV/STEL

Naphthalene sodium sulfonate NA NA

2-Butoxyethanol 25 ppm (120 mg/m3)/ 25 ppm (121 mg/m3)/

(Skin) (Skin)

Alcohol ethoxylate NA NA

NA - Not Available

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Herbal

APPEARANCE: Clear, Amber

pH: 9.0 to 9.9

PERCENT VOLATILE BY WEIGHT: 66 VAPOR PRESSURE: Not Available VAPOR DENSITY: Not Available BOILING POINT: Not Available

FREEZING/MELTING POINT: Not Available

SOLUBILITY IN WATER: Complete EVAPORATION RATE: Not Available

SPECIFIC GRAVITY: 1.08 VISCOSITY: Water Thin

OCTANOL/WATER PARTITION COEFFICIENT: Not Available

ODOR THRESHOLD: Not Available

10. STABILITY AND REACTIVITY

STABILITY (CONDITIONS TO AVOID):

Stable.

POLYMERIZATION:

Will not occur.

HAZARDOUS DECOMPOSITION:

None known.

INCOMPATIBLE MATERIALS:

Oxidizers (e.g., bleach).

11. TOXICOLOGICAL INFORMATION

ACUTE DATA:

This product is a moderate eye irritant. Based on acute toxicity testing of a similar product, this product may be harmful if swallowed. It is not considered to be toxic by skin absorption or inhalation. Acute dermal over-exposure to the alcohol ethoxylate has caused inflammatory changes of the lung in laboratory animals. Acute overexposure to 2-butoxyethanol has caused blood, liver and kidney effects in laboratory animals. The following additional data are available for product ingredients:

MSDS No: 4081 Page: 4 of 7

Date Prepared: 08/17/2000 Date Revised: 10/26/2000

PRODUCT/INGREDIENT	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)
Naphthalene sodium sulfonate	Not Available	Not Available	Not Available
2-Butoxyethanol	470 mg/kg	220 mg/kg	450 ppm (4-hr)
Alcohol ethoxylate	500–2000 mg/kg	921-3000 mg/kg	Not Available

SENSITIZATION DATA:

No data available.

CHRONIC DATA:

Prolonged overexposure to high concentrations of 2-butoxyethanol by skin absorption, ingestion and inhalation has caused blood, liver and kidney effects in laboratory animals.

REPRODUCTIVE/TERATOGENIC DATA:

No data available.

CARCINOGENIC/MUTAGENIC DATA:

Not listed as carcinogenic by NTP, IARC, or ACGIH or regulated as a carcinogen by OSHA.

SYNERGISTIC MATERIALS:

No data available.

12. ECOLOGICAL INFORMATION

No data available.

13. DISPOSAL CONSIDERATIONS

Disposal of this material should be in accordance with local, state or provincial and federal regulations. The unused product, as manufactured, is a RCRA non-hazardous waste in accordance with 40 CFR 261. The product has not been evaluated by the Toxicity Characteristic Leachate Procedure (TCLP). According to RCRA, it is the responsibility of the waste generator to ensure proper disposal.

14. TRANSPORT INFORMATION

DOT/TDG HAZARDOUS MATERIAL DESCRIPTION: Not regulated

15. REGULATORY INFORMATION

Not meant to be all-inclusive—selected regulations represented.

MSDS No: 4081 Page: 5 of 7

Date Prepared: 08/17/2000 Date Revised: 10/26/2000

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Under 40 CFR 370.2, this product meets the following hazard categories: Immediate, Delayed.

313 REPORTABLE INGREDIENTS: 2-Butoxyethanol is subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372 under the chemical category Glycol Ethers.

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

CERCLA REGULATORY: None of the ingredients in this product are reportable under CERCLA.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA STATUS: This product complies with all TSCA inventory requirements.

MASSACHUSETTS, NEW JERSEY, PENNSYLVANIA RIGHT-TO-KNOW:

INGREDIENT(S)	CAS NO.	STATE LISTING
Water	7732-18-5	Not Listed
Naphthalene sodium sulfonate	26264-58-4	Not Listed
2-Butoxyethanol	111-76-2	Ma, NJ, Pa
Alcohol ethoxylate	68439-50-9	Not Listed

NA - Not Applicable

CANADA

WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM):


Class D-Division 2B, eye irritant. This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

16. OTHER INFORMATION

HMIS RATING

HEALTH	*	2
FLAMMABILITY		0
REACTIVITY		0
PERSONAL PROTECTION		-

NFPA RATING



MSDS No: 4081 Page: 6 of 7

Date Prepared: 08/17/2000 Date Revised: 10/26/2000

MSDS STATUS

Revision #: 2

This MSDS replaces the January 04, 2000 MSDS. Any changes in information are as follows:

In Section 1

Prepared By Date Prepared [] Print CHEMTREC Phone Number

In Section 3

Potential Health Effects - Skin Absorption Signs & Symptoms - Inhalation Signs & Symptoms - Skin

In Section 9

(Group Field) for Vapor Pressure (Group Field) for Vapor Pressure Density Odor Threshold (Group Field) for Boiling Point (Group Field) for Evaporation Rate Coeff Oil/Water

In Section 10
Hazardous Decomposition Products

In Section 11 Toxicological

In Section 15
OSHA Hazard Comm. Rule WHMIS Class

APPROVED BY: EH&S/Regulatory Affairs APPROVAL DATE: 10/26/2000

The information on this data sheet represents our current data and best opinion as to the proper use in handling of the product under normal foreseeable conditions. Any use of this product which is not in conformance with this data sheet or product label, or which involves using the product in combination with any other product or any other process is the responsibility of the user.

MSDS No: 4081 Page: 7 of 7