09-115-008



MATERIAL SAFETY DATA SHEET

Page 1 of 7 **CND-N-067**

Prep	ared to OSHA,	ACC, ANSI, NOHSC, WHMIS & 20	001/58 EC 5	Standards	MSDS Revision: 5.0	MSDS	Revision Date	: 05/01/2007
		1	PPOD	IICT IDEN	ATTECATION			
	1. PRODUCT IDENTIFICATION Product Name:							
1.1								
	THINNER							
1.2	Chemical Name:	CHR.						
1.3	SOLVENT MIXT Synonyms:	UKE						
1.5	NONE							
1.4	Trade Names:							
	NA							
1.5	Product Use:						•	
		L OR SUNDRY USE ONLY						
1.6	Distributor's Name							
1.7	Distributor's Addre	L DESIGN, INC.						
17		WAY, VISTA, CA USA 92081						
1.8	Emergency Phone							
	CHEMTREC	+1 (800) 424-9300 / +1 (7	703) 527-	3887				
1.9	Business Phone:							
	800-833-NAIL	(6245), 760-599-2900						***************************************
		2	. HAZA	RD IDEN	TIFICATION			· · ·
2.1	Hozard Identificati							
		s classified as a hazardous sub: ustralia). Flammable liquid.	stance and	d as dangei	ous goods according	ng to the classi	tication criteri	a of NOHSC and
2.2	Routes of Entry:		alation:	YES	Absorption:	YES	Ingestion:	YES
2.3	Effects of Exposure		GIGHOH.	163	(Absorption.	1113	Tangeshors.	1113
2.5	INGESTION:	If product is swallowed, may co	ause nause	ea, vomiting	and/or diarrhea and	d central nervo	us system dep	ression.
	EYES:	May be irritating to the eyes. S						
	SKIN:	May cause irritation upon direc			•			_
	INHALATION:	Vapors of this product may be	e irritating	to the nose,	throat and other tis	sues of the res	piratory system	n. Symptoms of
		overexposure can include co	oughing, w	heezing, no	asal congestion, an	d difficulty bre	eathing, inha	lation of vapors
		exceeding the levels listed in	Section 2 ((Compositio	n and ingredient inf	ormation) can	cause central	nervous system
2.4	Symptoms of Over	depression (e.g., drowsiness, d	naziness, ne	ruuucnes, n	uoseuj.			
	EYES:	Overexposure in eyes may cau	use rednes:	s, itching an	d watering.			
	SKIN:	Symptoms of skin overexposure allergic skin reactions (e.g., ras	re may incl	lude rednes:	s, Itching, and Irritation	on of affected	areas. The pro	oduct can cause
2.5	Acule Health Effec		siles, Wells,	<u>uemums)</u>	opon protonged of the	epedied expos	ole.	
2.3	EYES:	Moderate irritation to eyes nea	r affected	areas.				
	SKIN:	Moderate irritation to skin near	affected a	ıreas.				
1	INHALATION:	High concentrations of vapors	can cause	drowsiness,	dizziness, headache	es and nausea.		
2.6	Chronic Health Effe	ects:						
	None known							· · · · · · · · · · · · · · · · · · ·
2.7	Target Organs:							
		respiratory system.			- (ii- C Ci'	1 / Emm A =1 =1545	N Doffotti	F Torono Maria
		ND = Not Determined; NE = Not						
NOTE	: all WHMIS red	quired information is included. It	t is located	in appropri	ate sections based a	n me ansi 2400).1-2004 forma	1.



Page 2 of 7

CND-N-067

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 5.0

MSDS Revision Date: 05/01/2007

3	COMPOSITION	ዴ ነለ	IGREDIENT	INFORMATION

					EXPOSURE LIMITS IN AIR					(mg/m³)	
				%	ACGIH		OSHA		OTHER		
CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.		TLV ppm	STEL ppm	PEL ppm	STEL ppm	IDLH ppm		
ETHYL ACETATE	141-78-6	AH5425000	201-550-6	40-60	400	NE	400	NE	2000	400 TWA	
ISOBUTYL ACETATE	110-19-0	AI4025000	203-745-1	20-40	150	NE	150	NE	NE	150 TWA	
METHYL ETHYL KETONE	78-93-3	EL6475000	201-159-01	10-25	200	300	200	300	NE		
	•			1				<u> </u>	L	<u> </u>	

4. FIRST AID MEASURES

4.1 First Aid:

INGESTION:

If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact Chemīrec at +1 (703) 527-3887 or the nearest Poison Control Center or local emergency number. Provide an estimate

of the time at which the material was ingested and the amount of the substance that was swallowed.

EYES:

If product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. If irritation occurs,

contact a physician.

SKIN:

If irritation occurs and product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the effected area with soap and water. If irritation, redness or swelling persists, contact a physician immediately.

INHALATION: Remove victim to fresh air at once.

Medical Conditions Aggravated by Exposure: 4.2

None known.

5. FIREFIGHTING MEASURES

Flashpoint & Method:

-9.4 °C (15 °F)

5.2 Autoianition Temperature:

NA

Flammability Limits: 5.3

Lower Explosive Limit (LEL):

NE

Upper Explosive Limit (UEL):

Fire & Explosion Hazards:

WARNING: EXTREMELY FLAMMABLE! Keep away from heat, lit cigarettes, sparks & open flame.


5.5 Extinguishing Methods:

CO₂, Halon, Dry Chemical, Foam

5.6 Firefighting Procedures:

This product is a Class B2 flammable liquid. When involved in a fire, this product will ignite readily and decompose to produce carbon oxides.

First responders should wear eye protection. Structural fire fighters must wear full protective equipment and MSHA/NIOSH-approved self-contained breathing apparatus. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas. If necessary, rinse contaminated equipment with soapy water before returning to service.



6. ACCIDENTAL RELEASE MEASURES

6.1

Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment.

For small spills (e.g., <1 gallon) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated ciothing and wash thoroughly before

For spills ≥ 1 gallon, deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.



Page 3 of 7

CND-N-067

MSDS Revision Date: 05/01/2007 Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 5.0 7. HANDLING & STORAGE INFORMATION Work & Hygiene Practices: Avoid prolonged contact with the product. Avoid breathing vapors of this product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product. Storage & Handling: Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans). Keep away from excessive heat, open flames, sparks, and other possible sources of ignition. Keep away from incompatible materials listed in Section 10. Do not store in damaged or unmarked containers or storage devices. Keep containers securely closed when not in use. Open slowly on a level, stable surface. Empty containers may retain residual amounts of product. Therefore, empty containers should be handled with care. Special Precautions: 7.3 NA 8. EXPOSURE CONTROLS & PERSONAL PROTECTION 8.1 When working with large quantities of product, provide adequate ventilation (e.g., local exhaust ventilation, fans). Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes. No special respiratory protection is required under typical circumstances of use or handling. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134, or applicable U.S. state regulations, or the appropriate standards of Canada, its provinces, E.C. member states, or Australia. Eye Protection: 8.3 Depending on the use of this product, splash or safety glasses may be worn. If necessary, refer to U.S. OSHA 29 CFR §1910.133, Canadian standards, or the European Standard EN166. 8.4 If anticipated that prolonged & repeated skin contact will occur during use of this product, wear latex or rubber gloves for routine industrial use. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, of the E.C. member states. 2 8.5 HEALTH No apron required when handling small quantities. 3 FLAMMABILITY When handling large quantities (e.g., ≥ 1 gallon), an apron should be worn and eye wash stations and deluge showers should be available. Upon completion of work REACTIVITY ٥ activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water. PROTECTIVE EQUIPMENT 9. PHYSICAL & CHEMICAL PROPERTIES 9.1 Density: ΝE 9.2 Boiling Point: NE 9.3 Melling Point: NE Evaporation Rate: NE (Butyl Acetate = 1) 9.4 9.5 Vapor Pressure: NE -9.6 Malecular Weight: NE Appearance & Color: 9.7 Clear liquid. 9.8 Odor Threshold: Solubility: 9.9 Moderately soluble in water. 9.10 ρН NΑ 911 Viscosity: Ŋ₽ Other Information: Vapor density 2.7 (Air = 1) (Calculated)



Page 4 of 7 **CND-N-067**

Prep	pared to OSHA, ACC, ANSI,	NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 5.0 MSDS Revision Date: 05/01/2007						
		10. STABILITY & REACTIVITY						
10.1	Stability:	Stable under ambient conditions when stored properly (see Section 7, Storage and Handling).						
10.2	Hazardous Decomposition Produc	Irritating vapors and toxic gases (e.g., carbon monoxide and carbon dioxide).						
10.3	Hazardous Polymerization:	Will not occur.						
10.4	Conditions to Avoid:	Exposure or contact to extreme temperatures, incompatible chemicals, strong light sources, sparks, flame.						
10.5	Incompatible Substances:	Strong oxidizers, peroxides or strong acids.						
		11. TOXICOLOGICAL INFORMATION						
11.1	Toxicity Dala:	This product has NOT been tested on animals to obtain toxicology data. There are toxicology data to						
11,1	loadily bala.	the components of the product, which are found in scientific literature. These data have not been presented in this document.						
11.2	Acute Toxicity:	See section 2.5						
11.3	Chronic Toxicity:	See section 2.6						
11,4	Suspected Carcinogen:	This product is not reported to be a suspected carcinogen.						
11.5	Reproductive Toxicity:	This product is not reported to cause reproductive toxicity in humans.						
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.						
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.						
	Teralogenicity:	This product is not reported to cause teratogenic effects in humans.						
	Reproductive Toxicity:	This product is not reported to cause retailogenic effects in humans. This product is not reported to cause reproductive effects in humans.						
11.6	Irritancy of Product:	See section 2.3						
11.7	Biological Exposure Indices:	NE						
11.8	Physician Recommendations:	Treat symptomatically.						
		12. ECOLOGICAL INFORMATION						
		12. ECOLOGICAL INTORMATION						
12.1	Environmental Stability:	The components of this product will slowly degrade over time into a variety of organic compounds Specific environmental data available for the components of this product are as follows:						
		Ethyl Acetate: Koc = 0.73. Water solubility: 64,000 mg/l. Bioconcentration Factor = 4-14 Bioconcentration is not anticipated to be significant. This compound can be removed from contaminated environments through volatilization, and biodegradation. This compound's half-life is water is 6.1 hours.						
12.2	Effects on Plants & Animals:	There are no specific data available for this product.						
12.3	Effects on Aquatic Life:	There are no specific data available for this product; however, very large releases of this product may be harmful or fatal to overexposed aquatic life.						
		13. DISPOSAL CONSIDERATIONS						
13.1	Waste Disposal:							
	-	accordance with appropriate Federal, state, and local regulations.						
13.2	Special Considerations:							
1	ILS FPA WASTE NUMBER!	2001 (characteristic - ignitable)						



Page 5 of 7

CND-N-067

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 5.0

MSDS Revision Date: 05/01/2007

14. TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.

CONSUMER COMMODITY, ORM-D (≤ 1.0 L) ORM-D UN1993, FLAMMABLE LIQUID, N.O.S. (ethyl acetate, methyl ethyl ketone), 3, II (> 1.0 L) CONSUMER COMMODITY, 9, ID8000 (≤ 0.5 L) UN1993, FLAMMABLE LIQUID, N.O.S. (ethyl acetate, methyl ethyl ketone), 3, II (> 0.51)

14.3

UN1993, FLAMMABLE LIQUID, N.O.S. (ethyl acetate, methyl ethyl ketone), 3, 11, LTD QTY (≤ 1.0 L) UN1993, FLAMMABLE LIQUID, N.O.S. (ethyl acetate, methyl ethyl ketone), 3, II (> 1.0 L)

TDGR (Canadian GND): 14.4

MARK PACKAGE "LIMITED QUANTITY" or "QUANTITÉ LIMITÉE" or "LTD QTY" or "QUANT LTÉE" (≤ 1.0 L)

UN1993, FLAMMABLE LIQUID, N.O.S. (ethyl acetate, methyl ethyl ketone), 3, II (> 1.01)

14.5

UN1993, FLAMMABLE LIQUID, N.O.S. (ethyl acetate, methyl ethyl ketone), 3, II, ADR, LTD QTY (≤ 1.0 L)

SCT (MEXICO):

UN1993, LIQUIDOS INFLAMABLES, N.E.P. (ethyl acetate, methyl ethyl ketone),3, II, CANTIDAD LIMITADA (≤1.0 L)

15. REGULATORY INFORMATION

15.1 SARA Reporting Requirements:

SARA 304 (40 CFR Table 302.4) - Ethyl Acetate; SARA 313 - Methyl Ethyl Ketone

15.2 SARA Threshold Planning Quantity:

There are no specific Threshold Planning Quantities for the components of this product.

TSCA Inventory Status: 15.3

15.5

The components of this product are listed on the TSCA Inventory.

CERCLA Reportable Quantity (RQ): 15.4

> Methyl Ethyl Ketone: 5000 lbs. Other Federal Requirements:

This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR subchapter G (Cosmetics)

15.6

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are tisted on the Priorities Substances List. Class B2 Flammable Liquid.



State Regulatory Information:

Ethyl Acetate and Methyl Ethyl Ketone are covered under specific state criteria. No components of this mixture are listed in the California Proposition 65 Lists.

67/548/EEC (European Union) Requirements:

The primary component of this product is not listed in Annex t of EU Directive 67/548/EEC:

Ethyl Acetate: Flammable (F). R: 11-36/37/38 — Highly flammable. Irritating to eyes, respiratory system and skin, S: 2-16-23-29-33 - Keep out of the reach of children. Keep away from sources of Ignition - No smoking. Do not breathe gas, tumes, vapor or spray. Do not empty into drains. Take precautionary measures against static discharges.

Methyl Ethyl Ketone: Flammable, Irritant (F, Xi). R: 11-36/37 – Highly flammable. Irritating to eyes and respiratory system. S: 2-9-16-25-33 - Keep out of the reach of children. Keep container in a wellventilated place. Keep away from sources of ignition - No smoking. Avoid contact with eyes. Take precautionary measures against static discharges.

Isobutyl Acetate: Flammable (F). R: Flammable. S: 9-16-33 - Keep container in a well-ventilated place. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.







Page 6 of 7

CND-N-067

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards

MSDS Revision: 5.0

MSDS Revision Date: 05/01/2007

16. OTHER INFORMATION

16.1 Other Information:

WARNING: EXTREMELY FLAMMABLE! Keep away from heat or flame. Use only as directed. Avoid eye contact. If contact occurs, flush eye thoroughly with running water. Use only in well ventilated area. Discontinue use immediately if irritation develops. Keep container closed. Store in a cool place. **KEEP OUT OF REACH OF CHILDREN**. Do not ingest. If swallowed, do not induce vomiting; seek medical attention. FOR PROFESSIONAL USE ONLY.

16.2 Terms & Definitions:

See last page of this MSDS.

16.3 Disclaimer:

This Material Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's & Creative Nail Design's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.

16.4 Prepared for:

Creative Nail Design, Inc.
A Division of Colomer U.S.A., Inc.
1125 Joshua Way
Vista, CA 92081 USA
800-833-NAIL (6245) phone
760-599-2900
760-599-4005 fax
http://www.cnd.com/

CND.

Hands, Feet. Beauty.

16.5 Prepared by:

ShipMate, Inc.

18436 Hawthorne Boulevard, Suite 201

Torrance, CA 90504 310-360-3700 phone 310-360-5700 fax

http://www.shipmate.com/



Dangerous Goods Training & Consulting



Page 7 of 7

CND-N-067

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS & 2001/58 EC Standards MSDS Revision: 5.0

MSDS Revision Date: 05/01/2007

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a MSDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

EXPOSURE LIMITS IN AIR:	
,	

ACGIH	American Conference on Governmental Industrial Hygienists
TLV Threshold Limit Value	
OSHA U.S. Occupational Safety and Health Administration	
PEL Permissible Exposure Limit	
IDIH immediately Dangerous to Life and Health	

FIRST AID MEASURES:

CPR

Cardiopulmonary resuscitation - method in which a person
whose heart has stopped receives manual chest compressions
and breathing to circulate blood and provide oxygen to the
body.

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

HEALTH, FLAMMABILITY & REACTIVITY RATINGS:


CAS No. | Chemical Abstract Service Number

0	Minimal Hazard	
1	Slight Hazard	
2	Moderate Hazard	
3	Severe Hazard	
4	Extreme Hazard	



PERSONAL PROTECTION RATINGS:


A	8			
В	8	65		
С	8		~	
D			~	
E	6			
F	6		~	





Safety Glasses
















Airline Hood/Mask or



Note: the dotted circle indicates that this respiratory protective equipment is required for high concentrations or for large volume spllls or releases of product.

Full Face

FLAMMABILITY LIMITS IN AIR:


Autolgnition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

OTHER STANDARD ABBREVIATIONS:

NA	Not Available
NR	No Results
NE	Not Established
ND	Not Determined
WL	Maximum Limit
SCBA	Self-Contained Breathing Apparatus

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA HAZARD RATINGS:

0	Minimal Hazard
3	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W-	Use No Water
OX	Oxidizer



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the							
LD50	exposed animals s							
1C50	Lethal concentration (gases) which kills 50% of the							
	exposed animal							
	Concentration expressed in parts of material per million							
ppm	parts							
TDie	Lowest dose to cause a symptom							
TClo	Lowest concentration to cause a symptom							
TD _{Io} , LD _{Io} , & LD _o or	Lowest dose (or concentration) to cause lethal or toxic							
TC, TC., LCio, & LCo	effects							
IARC	International Agency for Research on Cancer							
· NTP	National Toxicology Program							
RTECS	Registry of Toxic Effects of Chemical Substances							
BCF	Bioconcentration Factor							
TL _m	Median threshold limit							
log Kow or log Koc	Coefficient of Oil/Water Distribution							

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
CPR	Canada's Controlled Product Regulations

EC INFORMATION:

		內	1/2	A	e);		
С	E	F	N	0	T+	Χi	Xn
Corrosive	Explosive	fiammable	Harmful	Oxidizing	Toxic	irritani	Harmful

WHMIS INFORMATION:

		(8)	(1	®	(12)	R
Α	В	С	D1	D2	D3	Ε	F
Compressed	Flammable	Oxidizing	Toxic	initation	Infectious	Corrosive	Reactive