

MATERIAL SAFETY DATA SHEET

NOTE: BLANK SPACES ARE NOT PERMITTED. IF ANY ITEM IS NOT APPLICABLE, THE SPACE MUST BE MARKED TO INDICATE THAT.						
IDENTITY (As shown on Label or package) PLASTI DIP and PLASTI DIP UV (F-698, 819, 820)			PART NO. IF APPLICABLE			
SECTION I						
MANUFACTURER'S NAME Plasti Dip International Inc.			EMERGENCY PHONE No. USA only: 1-800-424-9300 INT'L: 703-527-3887			
ADDRESS (NUMBER, STREET, CITY, STATE AND ZIP CODE) 3920 Pheasant Ridge Drive			REVISION #			
Blaine, MN 55449			MANUFACTURER'S PHONE No. FOR INFORMATION 1-763-785-2156			
			DATE MSDS WAS PREPARED October 17, 2008			
SECTION II - HAZARDOUS INGREDIENTS INFORMATION. All Health Hazards which comprise 1% or greater of the composition and all carcinogens if 0.1% of the composition or greater.						
HAZARDOUS COMPONENTS CHEMICAL and IDENTITY AND COMMON NAME (S)		% Wt. (OPTIONAL)	CAS NO.	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMEND
VM&P Naphtha		32 – 38	64742-89-8	300 ppm	300 ppm	None
Hexane		16-19	110-54-3	500 ppm	50 ppm	None
Toluene		13-16	108-88-3	200 ppm	50 ppm	None
Methyl Ethyl Ketone		3-7	78-93-3	200 ppm	200 ppm	None
Resins		25-27	N/A	N/A	N/A	None
SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS						
BOILING POINT 149-285°F		SPECIFIC GRAVITY (H₂O =1) 0.79 – 0.83		APPROXIMATE WEIGHT PER GALLON (LBS) 6.60 – 6.90		
VAPOR PRESSURE 125 mmHg @ 20°C		VAPOR DENSITY (AIR = 1) Heavier than air		EVAPORATION RATE (BUTYL ACETATE =1) >1.0		
SOLUBILITY IN WATER Insoluble		% VOLATILE 72 – 75 VOC LBS./GAL 4.8-5.2		OTHER (IF ANY) None		
APPEARANCE AND ODOR Various colors, Honey Like Substance – Characteristic Odor						
SECTION IV-FIRE AND EXPLOSION HAZARD DATA						
FLASH POINT (METHOD USED) -10.0°F TCC		FLAMMABLE LIMITS		LEL 0.9	UEL 11.5	
EXTINGUISHING MEDIA Carbon Dioxide, Dry Chemical, or Foam						
SPECIAL FIRE FIGHTING PROCEDURES Self contained breathing apparatus with a full face piece, operated in pressure demand or other positive pressure mode.						
UNUSUAL FIRE AND EXPLOSION HAZARDS This material is flammable and may be ignited by heat, sparks, flame or static electricity.						
HAZARDOUS PRODUCTS FORMED BY FIRE OR THERMAL DECOMPOSITION Carbon Dioxide and/or Carbon Monoxide						
EXPLOSIVE LIMITS (% BY VOLUME IN AIR) 0.9 – 11.5						
SECTION V - OPTIONAL HAZARD RATINGS IDENTIFICATION						
HAZARD RATING 4-EXTREME 3-HIGH 2-MODERATE 1-SLIGHT 0-INSIGNIFICANT **SEE SECTION IV			National Fire Protection Association (NFPA) FIRE <u> 3 </u> REACTIVITY <u> 0 </u> HEALTH <u> 2 </u> SPECIAL HAZARDS <u> None </u>			

This is the "front" when printed in duplex. Page 1 of 2 pages if not duplex.

SECTION VI - REACTIVITY AND STABILITY DATA			
STABILITY	UNSTABLE	STABLE X	
INCOMPATIBILITY (Materials to Avoid) Strong acids, bases, oxidizing agents, selected amines with alkali metals and halogens.			
HAZARDOUS DECOMPOSITION OR BY PRODUCTS Carbon Monoxide, Carbon Dioxide			
HAZARDOUS POLYMERIZATION	MAY OCCUR WILL NOT OCCUR X	CONDITIONS TO AVOID May be ignited by heat, sparks, flame or static electricity.	
SECTION VII - HEALTH HAZARD DATA			
ROUTES OF ENTRY	INHALATION? YES	SKIN? YES	INGESTION? YES EYES? YES
HEALTH HAZARDS	ACUTE X	CHRONIC X	
CARCINOGENICITY: No			
SIGNS AND SYMPTOMS OF EXPOSURE Headache, Dizziness, Drowsiness, Fatigue, Irregular Heartbeat, Skin and Eye Irritation.			
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE			
EMERGENCY AND FIRST AID PROCEDURES	Ingestion: Contact Physician or Poison Control Immediately. Inhalation: Remove to fresh air. Administer Oxygen or Artificial Respiration if Necessary. Eye Contact: Flush with large amounts of water. If irritation persists, contact Physician. Skin: Wash with soap and water.		
SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE			
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED	Wipe up with floor absorbent. Transfer to hood. Prevent run-off to sewers. Eliminate all sources of ignition. Ventilate to maintain exposure below PEL's. Use sand or other material to dam or contain spills. If large spill, notify appropriate state and local agencies.		
WASTE DISPOSAL METHODS Dispose of product in accordance with local, county, state and federal regulations.			
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE	Avoid eye contact with eyes. Keep container closed. Use with adequate ventilation. Keep away from sparks, flame and heat sources and store in a cool area. Avoid inhalation of vapors and personal contact with liquid product. Use good personal hygiene practices.		
OTHER PRECAUTIONS	Keep Container Closed When Not In Use. Containers should be disposed of in an environmentally safe manner in accordance with Governmental Regulations.		
SECTION IX - CONTROL MEASURES			
RESPIRATORY PROTECTION (SPECIFY TYPE) Depending on the Airborne concentration, use a Respirator with appropriate NIOSH approved cartridge or supplied air equipment.	PROTECTIVE GLOVES Impervious Gloves		
VENTILATION	LOCAL EXHAUST Supplemental (if needed)	SPECIAL None	
	MECHANICAL (GENERAL) To maintain exposure below PEL's	OTHER None	
EYE PROTECTION Chemical splash goggles, or approved eye protection.	OTHER PROTECTIVE CLOTHING OR EQUIPMENT Chemical Apron/Eye bath/Safety Shower		
WORK HYGIENIC PRACTICES Wash thoroughly after handling.			
SECTION X - TRANSPORTATION INFORMATION			
DOT PROPER SHIPPING NAME Coating Solution	DOT HAZARD CLASS 3		
DOT UN NUMBER UN 1139	DOT PACKING GROUP II		
IATA PROPER SHIPPING NAME Coating Solution	IATA HAZARD CLASS 3		
IATA UN NUMBER UN 1139	IATA PACKING GROUP II		
SECTION XI - 313 SUPPLIER NOTIFICATION			
THIS PRODUCT CONTAINS THE FOLLOWING CHEMICALS SUBJECT TO REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT -TO-KNOW ACT OF 1986, 40 CFR 372, (see table on page 1 for CAS # and percent by weight). Hexane, Toluene, and Methyl Ethyl Ketone			
WARNING: THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM.			

This is the "back" when printed in duplex. Page 2 of 2 pages if not duplex.

Prepared By: Michael N Hindin

THE INFORMATION PROVIDED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THE DATA OR THE RESULTS OBTAINED FROM ITS USE. SINCE THE INFORMATION CONTAINED HEREIN MAY BE APPLIED UNDER CONDITIONS BEYOND THE VENDORS CONTROL AND SINCE SUBSEQUENT DATA MAY SUGGEST MODIFICATION OF THE INFORMATION, VENDOR ASSUMES NO RESPONSIBILITY FOR THE RESULTS OF ITS USE.